

ImportClientProblemList Table

This table allows for importing client diagnoses into the Problem List format.

Data Dictionary Requirements

- The fields for **ImportClientProblemList** must first be added to the Data Dictionary.
- If the internal client Credible ID is not being used for the import then the lookup must be set accordingly in the Data Dictionary.

Import Notes

- The import tool must have **psp_import_clientproblemlist** as the Post Query.
- All diagnoses will import as Axis 3.
- ICD-9 codes must match a valid code from the Axis 3 list (ICD9CM table).
- ICD-10 codes must match a valid code from the ICD-10 master listing.
- ICD-9 or ICD-10 or both can be imported for each problem. If both are imported, the imported ICD-10 code will be used. If only the ICD-9 code is imported, the GEM mapped ICD-10 code will be used if one is set (Admin > Axis 3). If only the ICD-10 code is imported, the problem will only have ICD-10.
- One assessment per client per import row will be created; each row must contain all the diagnoses relevant for that assessment. Importing in one row for a client's primary problem and another row for the secondary problem will result in two assessments in Credible, each with just one diagnosis.
- If importing more than one assessment per client, the active assessment will be the import row with the most recent *effective_date*.

Client Profile

The diagnosis fields on the Client Profile will be updated with the active assessment's problems as follows:

axis_1 = problem #1; axis_1b = problem #2; axis_1c = problem #3; axis_1d = problem #4;
axis_1e = problem #5; axis_1f = problem #6; axis_2 = problem #7; axis_2b = problem #8;
axis_3 = problem #9; axis_4 = problem #10; axis_5 will be left blank

Due to space limitations of these fields, only one code and description will be displayed, with preference given to ICD-10 codes and descriptions. If the problem has both ICD-10 and ICD-9 codes and descriptions, only the ICD-10 code and description will appear in the profile field.

Fields and Usage Notes

Field	Usage
client_id	Required
effective_date	Optional; a dash or slash is needed between month, day, and year (6-1-10 or 6/1/10); leading zeros on month and day are optional; year can be two- or four-digit; must be used if importing in more than one assessment per client
problem_1_icd9	Optional (required if no ICD-10 code is imported); the ICD-9 code for the primary problem
problem_1_icd10	Optional (required if no ICD-9 code is imported); the ICD-10 code for the primary problem
problem_1_diagnosed_by	Optional; free text with a maximum of 50 characters
problem_1_is_ro	Optional; 0 = False (default); 1 = True - this diagnosis is a rule out
problem_1_diagnosed_date	Optional; the date this problem was diagnosed
problem_1_onset_date	Optional; the onset date for this problem
problem_1_onset_prior_to_admission	Optional; a one character code to indicate whether this problem started prior to the client being admitted Y = Yes N = No U = Unknown
problem_1_previous_onset_date	Optional; the previous onset date for this problem

Note: The *problem_....* fields repeat 15 times, with the number indicating the order in the problem list for that diagnosis.